TotalMix FX

Mixing/Routing with superior features for Studio and Live Work

Since 2001 TotalMix added unlimited routing and mixing to RME's audio interfaces. Its unique capability to create as many independent submixes as output channels available turned it into the most flexible and powerful mixer of its kind.

With supported hardware, TotalMix FX includes a complete effects system, which not only adds flexibility to the recording chain, but also makes latency saddled software solutions obsolete. TotalMix FX (FX on supported cards) can completely replace an external mixer, enabling the creation of multiple latency-free monitor mixes with EQ, Dynamics, Reverb and Delay for any outputs incl. main monitors and headphone mixes for musicians.

Overview of TotalMix FX support for RME devices:

RME USB, FireWire & Thunderbolt technology Interfaces

Fireface 802	●
Fireface UFX[1]	●
Fireface UFX II	●
Fireface UFX+	●
Fireface UCX	●
Fireface UC	○
Fireface 800[1]	○
Fireface 400[1]	○
Babyface[1] (no Dynamics)	●
Babyface Pro (no Dynamics)	●
MADIface Pro (no Dynamics)	●
MADIface XT	●
MADIface USB	○
Digiface USB	○

RME PCI & Cardbus

HDSP 9632	○
HDSP 9652	○
HDSP PCI-Card[1,2]	○
HDSP Cardbus[1,2]	○
HDSP AES-32	○
HDSP MADI[1]	○

RME PCI Express

HDSPe AIO	○
HDSPe RayDAT	○
HDSPe PCI-Card[2]	○
HDSPe ExpressCard[2]	○
HDSPe AES	○
HDSPe MADI	○
HDSPe MADIface[1]	○
HDSPe MADI FX	●
MADIface XT	●

●	with DSP Effects	○	without DSP Effects

[1] Discontinued - Out of Production, [2] Hostcard for Multiface II , Multiface, Digiface, RPM

RME